



AWIS MAINS



HAWLE-VARIO

- ▶ ADJUSTABLE FLANGE TO FLANGE LENGTH
- ▶ AVAILABLE IN SHORT AND LONG VERSIONS
- ▶ ALLOWS FOR DEFLECTION OF UP TO 10°



SYSTEM 2000 FLANGE ADAPTORS



SYSTEM 2000 COUPLINGS

- ▶ TOTAL RESTRAINT
- ▶ MINIMAL PIPE INSERTION FORCE
- ▶ EASY TO DISMANTLE



HAKU PIPE SADDLE WITH FLANGED OUTLET

- ▶ FOR PE PIPES UP TO PN16
- ▶ DN100-600



HAKU PIPE SADDLE WITH THREADED BSP OUTLET

- ▶ FOR PE PIPES UP TO PN 16
- ▶ DN 40-500



SYNOFLEX COUPLERS

- ▶ EASY TO INSTALL
- ▶ 10 YEAR HAWLE WARRANTY
- ▶ PATENTED RESTRAINT SYSTEM
- ▶ MADE FOR GENERATIONS
- ▶ THE PERFECT CONNECTION FOR 'ANY PIPE TO ANY PIPE'



For more details and available sizes please contact AWIS

HAWLE - MADE FOR GENERATIONS



DN 50-300



DN 50-300



DN 50-200



DN 50-300



DN 50-300



DN 50-200



DN 50-200



DN 50-600



DN 50-600



DN 50-300
with lateral threaded
connection for flushing the
line, pressure testing, etc.



DN 80/90
DN 100/110

HAWLE FITTINGS ARE:

- ▶ EASY TO INSTALL IN ALL WEATHER CONDITIONS
- ▶ HAWLE 10 YEAR WARRANTY
- ▶ HAWLE PATENED RESTRAINT SYSTEM

Disclaimer: While every effort has been made to ensure that the information in this brochure is correct and accurate. Users of AWIS Pty Ltd provided product or information within this document must make their own assessment of suitability for their particular application. Product dimensions are nominal only, and should be verified if critical to a particular installation. No warranty is either expressed, implied, or statutory made by AWIS Pty Ltd Products unless expressly stated in any sale and purchase agreement entered into between AWIS Pty Ltd and the

Distributed by AWIS Pty Ltd



**Australian Water &
Irrigation Solutions** PTY LTD

A: PO Box 98(1/15 Stud Rd) Bayswater VIC 3153

P: +61 3 9720 2803

F: +61 3 9729 0121

M: David- 0417 052 443 Terry-0412 854 241

E: david@awis.com.au terry@awis.com.au